

POSEIDON 7



Nilfisk
ALTO
works for you

POSEIDON 7

Industrial cold water pressure washer

Powerful Cleaning - Pressure levels of up to 195 bar provide heavy duty cleaning bringing working time down considerably.

Dual detergent tanks - Comes with two way detergent valves. Tanks are easily removable for emptying and filling. It is also easy to see the level of detergent remaining in each tank, thus allowing the user to pre-fill enough detergent before leaving for the work place.

Food industry specialist - The POSEIDON 7 is available with added extras for use in the food industry, including non marking rubber wheels and hose, external detergent injector and stainless steel frame.

Easy access - Easy to open cabinet for quick & simple access for service and greater accessibility to service parts, saving time & costs.

Ergo 2000 Spray Gun - The ultimate in ergonomics, user friendliness and adaptability. The spray gun has a 360 degree swivel reducing fatigue, plus with Ergo coupling just one click and the hose is connected for quick set up.

Accessory Storage - 2 lance holders ensure easy and convenient storage of accessories.

TECHNICAL DATA	POSEIDON 7-67 FA	POSEIDON 7-67 FAXT	POSEIDON 7-67 FFA	POSEIDON 7-67 FBFA
Pump pressure (bar/MPa)	195/19.5	195/19.5	195/19.5	195/19.5
Cleaning impact (kg/force)	6.7	6.7	6.7	6.7
Water flow Qmax/Qiec (l/h)	1280/1180	1280/1180	1280/1180	1280/1180
Max. inlet temperature (°C)	85	85	85	70
Pump (RPM)	1450	1450	1450	1450
Dimensions L x W x H (mm)	775 x 570 x 1020	930 x 570 x 1020	775 x 570 x 1020	930 x 649 x 1020
Weight (kg)	89	95	89	94
Power consumption (kW)	8	8	8	8
Voltage/phase/frequency/current (V/~Hz/A)	400/3/50/14	400/3/50/15	400/3/50/14	400/3/50/14
El cable (m)	8	8	8	8
Suction height dry (m)	1	1	1	1
FEATURES				
Pistons / number of pistons	Ceramic / 4	Ceramic / 4	Ceramic / 4	Ceramic / 4
Automatic start/stop	•	•	•	•
Low pump oil safety	•	•	•	•
Water flow regulation	•	•	•	•
Water brake tank				•
Detergent injector (external)				•
Detergent tank (l)	2 x 2.5	2 x 2.5	2 x 2.5	2 x 2.5
Additional hose and rotary jet lance		•		
Hose reel		•		
STANDARD EQUIPMENT				
HP hose (DN10)	• [10 m]	• [15 m]	• [10 m]	• [10 m]
Ergo 2000	•	•	•	•
Ergo coupling	•	•	•	•
Water inlet coupling	•	•	•	•
Hose reel		•		
Tornado Plus lance without HP nozzle	•	•	•	•
TurboHammer Plus lance with HP nozzle		•		
Tornado Plus nozzle	•	•	•	•
ITEM NO.	107146800	107146801	107146802	107146812


FAXT: Flow activated, time delayed shut down , comes with hose reel, additional hose & rotary jet lance.

FFA: Flow activated, time delayed shut down. Food industry suitable with stainless steel frame and grey non marking hose and wheels.

FA: Flow activated, time delayed shut down

FBFA: Flow activated, time delayed shut down. Food industry suitable with stainless steel frame and grey non marking hose and wheels, with on-board water break tank and foam injector.

DURABLE PUMP



The POSEIDON 7 FA is still equipped with the renowned, industrial class, **C3 pump** based on a tough 4 piston pump construction, double roller bearings, flow activated control system and 1450 rpm motor.

MANOEUVRABILITY



The front castor wheel also allows optimal manoeuvrability over uneven ground.



The large, wide rear wheels give excellent ground clearance and great maneuverability even over rough ground.

Optional Accessories (see product catalogue for further accessories)



Crane Roundsling

Ideal for easily manoeuvring machines using cranes or loaders



Foam lance

Used together with Foam Injector & by-pass for cleaning surfaces & equipment



Vehicle Accessories

Under carriage lances for hard to reach areas of stubborn dirt



Wash Brush

Allows the mechanical cleaning of domestic and commercial vehicles to remove stubborn dirt and traffic film

Distributed by:

No claims can be made on the basis of information or illustrations contained in literature. Subject to alteration of technical data, design and equipment

www.nilfisk-alto.co.uk
www.nilfisk-alto.ie

Nilfisk
ALTO
works for you